

POCKET NC V2-10 SPECIFICATIONS

MAX TRAVEL

X: 4.55 in (115.5mm)

Y: 5.05 in (128.3 mm)

Z: 3.55 in (90.1mm)

A: -25° to 135°

B: Continuous Rotation

▶ Tested on G5 titanium, 6061 aluminum, 303 stainless, machinable wax, acetal

Accepts standard G Code. Test G Code at sim.pocketnc.com



www.pocketnc.com info@pocketnc.com Phone: +1.406.451.3799



pocket no

| AXIS | MAXIMUM TRAVEL | SPEED |
|------|--|-----------------------------|
| X | 4.55 in (115.5 mm) | 60 in/min (1524 mm/ min) |
| Υ | 5.05 in (128.3 mm) | 60 in/min (1524 mm/ min) |
| Z | 3.55 in (90.1 mm) | 60 in/min (1524 mm/ min) |
| А | -25° to 135° | 40°/second |
| В | Continuous rotation (-9999° to 9999°) | 40°/second |

| AXIS | BACKLASH |
|------|---|
| X&Y | 0.0005 in (12.7 µm) at tool base |
| Z | Backlash at 18 pound (8.16 kg) load: 0.0005 in (12.7 µm) |
| А&В | 0.01° |

| AXIS | RESOLUTION AND REPEATABILITY |
|------|--|
| XYZ | Resolution: 0.00024 in (6.10µm) Homing Repeatability: ±0.0005 in (12.7µm) Repeatability: ±0.002 in (50.8µm) at 0% load |
| A&B | Resolution: 0.01° Homing Repeatability: ±0.05° Repeatability: ±0.05° at 0% load Runout: < 0.002 in (50.8 µm) |

| SPINDLE | | | |
|----------------|--------------------------------------|--|--|
| Spindle Speed | 2,000-10,000 RPM | | |
| Power | 200 W | | |
| Spindle Motor | BLDC 3 Phase with Hall Feed- back | | |
| Spindle Runout | ~0.0005 in (12.7 µm) | | |
| Tool Change | 3mm Hex Key ER11 Collet | | |

| MACHINE CONTROL | | |
|--|--|--|
| Texas Instruments Arm Cortex A8 running Machinekit/Rockhopper | | |
| Accepts Standard Gcode | | |
| Features | Spindle Override Feed Override Stop, Start, Pause Jog while pause 5 axis simultaneous movement | |
| Connectivity | Ethernet, USB, and mini USB | |
| Power Source | 90-264 VAC, 127-370 VDC, 47-63Hz | |

| squareness in all axes | | | |
|--|---|--|--|
| Machine Footprint: 17.5 in (444.5 mm) x 12.5 in (279.3 mm) | | | |
| 5 NEMA 17 Motors | 3 linear lead screws with preloaded nuts 2 Rotary Worm Drives | | |
| Linear Bearings | 9 and 42mm, 10% preload | | |
| Integrated angular contact rotary bearings | | | |

PURCHASE INCLUDES:

COMPONENTS

One extended reach tool holder 1/8 inch ER11 collet and nut 1/8 inch square end mill, single flute Pocket NC vise and hardware Pocket NC limited 1-year warranty



